



Sistema / System



Microlit LED



SISTEMA LINEAL LED DE SUSPENDER (MCR) O ADOSAR (MCD) SURFACE (MCD) OR PENDANT (MCR) MOUNTING LINEAR LED SYSTEM

Módulos de alta potencia / High power modules

	Consumo Consumption	Flujo luz Light output *	Temperatura color Colour temperature	L - Longitud L - Length
MCD/MCR15 3RH	15W	1.200lm	3.000/4.000°K	700 mm
MCD/MCR25 3RH	25W	1.850lm	3.000/4.000°K	980 mm
MCD/MCR35 3RH	35W	2.450lm	3.000/4.000°K	1.260 mm
MCD/MCR40 3RH	40W	3.100lm	3.000/4.000°K	1.540 mm
MCD/MCR50 3RH	50W	3.700lm	3.000/4.000°K	1.820 mm

Módulos LED de aplicación en superficie o suspendida. Fabricados en perfil de aluminio. Difusor de metacrilato Opal. Vida útil de 50.000 horas con alto flujo de emisión de luz. Índice de reproducción cromática cri>85. Drivers electrónicos incorporados. Opción versión regulable Dali y Touch & Dimm.

Módulos de media potencia / Medium power modules

	Consumo Consumption	Flujo luz Light output *	Temperatura color Colour temperature	L - Longitud L - Length
MCD/MCR15 3R	15W	1.050lm	3.000/4.000°K	980 mm
MCD/MCR20 3R	20W	1.500lm	3.000/4.000°K	1.260 mm
MCD/MCR25 3R	25W	1.800lm	3.000/4.000°K	1.540 mm
MCD/MCR30 3R	30W	2.200lm	3.000/4.000°K	1.820 mm
MCD/MCR40 3R	40W	3.000lm	3.000/4.000°K	2.380 mm
MCD/MCR50 3R	50W	3.600lm	3.000/4.000°K	2.940 mm

Pendant aluminium LED modules. Opal metacrylate diffuser. Long life LED technology 50.000 hours and high lumen output. Rendering colour index cri>85. Electronic driver built-in also available as an option dimmable. Touch & Dimm and DALI drivers.

*Flujo efectivo salida luminaria. / Effective luminaire output flux.

COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

.30 3.000°K CRI>85	MCD Superficie Surface mounting
.40 4.000°K CRI>85	MCR Suspensión Suspended mounting
.ER regulable 1-10/dimmable	.ERDA regulable DALI y pulsador DALI and touch & dimm

EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

MCD 15.30 3R GM: Montage superficie (adosado) 3000°K 15W Gris metalizado
Surface mounting 3000°K 15W Metallic grey
MCR 15.40 3RH B: Montage suspendido 4000°K 15W Blanco
Suspended mounting 4000°K 15W White

ACCESORIOS ver pág. 151 / 153
ACCESSORIES see page 151 / 153

ACABADOS / FINISHES



DIRECCION LUZ / LIGHT DIRECTION



TECNOLOGÍA / TECHNOLOGY

